


616.23.3.25 (TA-25) Crosswalk Closures and Pedestrian Detours

SPEED	SIGN SPACING (ft.)		TAPER LENGTH (ft.)		OPTIONAL BUFFER LENGTH (ft.) (B)	CHANNELIZER SPACING (ft.)	
	Undivided (S)	Divided (S)	Shoulder ¹ (T1)	Lane ² (T2)		Tapers	Buffer/ Work Areas
0-35	200	200	-	-	120	15	25
40-45	350	500	-	-	220	20	50
50-55	500	1000	-	-	335	50	100
60-70	1000	1000	-	-	550	60	100

¹ Shoulder taper length based on 10 ft. (standard shoulder width) offset ² Lane taper length based on 12 ft. (standard lane width) offset



Where sidewalks exist, provisions **should** be made for disabled persons.

Curb parking **shall** be prohibited for at least 50 ft. in advance of the mid-block crosswalk.

Pedestrian traffic signal displays controlling closed crosswalks **should** be covered or deactivated.

Only the temporary traffic control devices related to pedestrians are shown. Other devices, **may** be necessary to control traffic.

Signs **may** be mounted on portable mounts at 1 ft. provided they do not interfere with pedestrian movement or be obstructed by parking. Otherwise, signs **shall** be mounted at 7 ft.

For high speed facilities, channelizer spacing **may** be reduced to 1/2 spacing noted in table.

Other appropriate signs **may** be used in lieu of the SHOULDER WORK AHEAD sign.

