

NOTES:
 (1) FLAGS SHALL ENHANCE ALL SIGNS WITHIN THE FIRST ADVANCED WARNING AREA.
 (2) FLAGS SHALL ENHANCE THE SIGN.
 (3) ADVANCE WARNING RAIL SYSTEM SHALL ENHANCE THE FIRST OCCURRENCE OF SIGN IN THE WORK ZONE, ACCORDING TO EPG 616.2.9.
 (4) USE ONLY WHEN SPEED REDUCTION IS 15 MPH OR GREATER BELOW POSTED OR NORMAL SPEED LIMIT.
 (5) USE WHEN DESIGN SPEED IS 30 MPH OR LESS. CONSIDER USING SIGN ④A.
 (6) USE WHEN DESIGN SPEED LIMIT IS GREATER THAN 30 MPH, CONSIDER USING SIGN ④A.
 (7) USE W01-8a CHEVRON ON DIVIDED HIGHWAYS.
 FOR DETAILS AND DIMENSIONS, SEE STANDARD PLAN 616.10.

Signs and Devices Legend

Figure 616



MO4-10R (RIGHT)
MO4-10L (LEFT)

(17)



WO20-2

(18)



WO20-3

(20) (1)



WO21-5b

(21)




WO8-9

(22)



WO8-9a

(23)



WO12-2



WO12-2x

(24)



(NORMAL SPEED)
R2-1

(25)




GO20-2

(26)



MO4-9R (RIGHT)
MO4-9L (LEFT)

(27)



(6)

WO12-2



WO12-2x

(28)



R11-2

(29)



(8)

WO12-3a
WO12-3b


(30)

(8)



WO6-3

(31)



WO1-4bR (RIGHT)
WO1-4bL (LEFT)

(32)



WO1-4cR (RIGHT)
WO1-4cL (LEFT)

(33)

NOTES:

(8) TYPE B WARNING LIGHTS

FOR DETAILS AND DIMENSIONS, SEE
STANDARD PLAN 616.10.

Signs and Devices Legend

Figure 616



W05-5
34 (3)



W08-12
35




W08-11
36



W01-2L (LEFT)
W01-2R (RIGHT)
37 (6)



W01-1L (LEFT)
W01-1R (RIGHT)
38 (5)



W03-1a
39



W03-2a
40



R1-1
41

3-WAY

OR

4-WAY

R1-3

41A (9)



R4-7a
42

BRIDGE

OR

RAMP



W05-1
43



W013-1
44 (10) (11)



W07-3a
44A (10)



R4-1
46



R4-2
46A



R10-6
47



OR LOW CLEARANCE

48

NOTES:

- (9) ONLY FOR USE WITH STOP SIGN WHEN CONDITION EXISTS. FOR ONE-WAY OR TWO-WAY STOP, A PLATE IS NOT USED.
 - (10) ONLY USED IN COMBINATION WITH WARNING SIGN.
 - (11) SHOULD BE USED WHEN THE DESIGN SPEED IS LESS THAN THE POSTED WORK ZONE SPEED.
- FOR DETAILS AND DIMENSIONS, SEE STANDARD PLAN 616.10.

Signs and Devices Legend

Figure 616




E05-1

49



M04-8a

52



CONST -3A

53 (1)

OR




CONST -3X

53A



G023-1

54



TEMPORARY RAISED PAVEMENT MARKERS



TUBULAR MARKERS




CHANNELIZERS (12)




DIRECTIONAL INDICATOR BARRICADES

TYPE F TEMPORARY CONCRETE TRAFFIC BARRIER




END TREATMENT



CHANGEABLE MESSAGE SIGN (CMS)



TYPE III MOVABLE BARRICADE



FLASHING ARROW PANEL



FLAGGER

NOTES:
(12) CONES ALLOWABLE FOR DAYLIGHT OPERATIONS ON MINOR ROADS ONLY.

FOR DETAILS AND DIMENSIONS, SEE STANDARD PLAN 616.10.

Signs and Devices Legend

Figure 616