

## 616.8.13 (TA-13) Temporary Road Closure - DE/CM

SPEED	SIGN SPACING (ft.)		TAPER LENGTH (ft.)		OPTIONAL	CHANNELIZER SPACING (ft.)	
	Undivided (S)	Divided (S)	Shoulder (1) (T1)	Lane (2) (T2)	BUFFER LENGTH (ft.) (B)	Tapers	Buffer/ Work Areas
0-35	200	-	-	-	280	-	40
40-45	350	-	-	-	400	-	80
50-55	500	-	-	-	560	-	80
60-70	1000	-	-	-	840	-	120

1 Shoulder taper length based on 10 ft. (standard shoulder width) offset. 2. Lane taper length based on 12 ft. (standard lane width) offset.

**NOTES:**

CONDITIONS REPRESENTED ARE A PLANNED CLOSURE NOT EXCEEDING 20 MINUTES DURING THE DAYTIME.

SEE EPG 616.12 WORK ZONE SPEED LIMITS FOR SPEED LIMIT GUIDELINES.

A CMS MAY BE USED IN ADDITION TO THIS SIGNING.

PROVIDE SIGNS ON LEFT AND RIGHT SIDE OF DIVIDED HIGHWAYS.

ROAD WORK AHEAD SIGN NOT NEEDED IF CLOSURE IS LOCATED WITHIN THE LIMITS OF AN ACTIVITY AREA WHERE ANOTHER ROAD WORK AHEAD SIGN IS ALREADY USED.

A FLAGGER OR UNIFORMED LAW ENFORCEMENT OFFICER SHALL BE USED FOR THIS APPLICATION. THE FLAGGER, IF USED FOR THIS APPLICATION, SHALL FOLLOW THE PROCEDURES PROVIDED IN EPG 616.5.07 AND 616.5.08. THE UNIFORMED LAW ENFORCEMENT OFFICER, IF USED FOR THIS APPLICATION, SHOULD FOLLOW THE PROCEDURES PROVIDED IN EPG 616.5.07 AND 616.5.08.

SEE EPG 616.12 WORK ZONE SPEED LIMITS FOR SPEED LIMIT GUIDELINES.

