


Surveying Along Centerline of Low Volume, Two-Way Highways

SPEED	SIGN SPACING (ft.)		TAPER LENGTH (ft.)		OPTIONAL BUFFER LENGTH (ft.) (B)	CHANNELIZER SPACING (ft.)	
	Undivided (S)	Divided (S)	Shoulder ¹ (T1)	Lane ² (T2)		Tapers	Buffer/ Work Areas
0-35	200	-	-	-	-	-	50
40-45	350	-	-	-	-	-	100
50-55	500	-	-	-	-	-	100
60-70	1000	-	-	-	-	-	100

¹ Shoulder taper length based on 10 ft. (standard shoulder width) offset ² Lane taper length based on 12 ft. (standard lane width) offset

TYPE ROADWAY	SIGN HEIGHT	MAXIMUM WORK ZONE LENGTH (L)
URBAN	1' Portable 7' Post	1 Mi.
RURAL UNDIVIDED	1' Portable 5' Post	3 Mi.



Notes:

When surveying on road having an ADT of 500 or greater or when 10 ft. of driving surface cannot be maintained, one lane **shall** be closed. Refer to appropriate lane closure typical applications.

ROAD WORK AHEAD signs **may** be used in place of the SURVEY CREW AHEAD signs.

For short duration and mobile operations, signs and channelizing devices **may** be reduced or eliminated if a work vehicle with activated rotating lights or strobe lights is used.

For mobile operations, spacing between flagger and FLAGGER AHEAD sign **shall** not exceed one mile.

